



SECTION: STANDARD PEDESTRIAN PATH



(images are illustrative only and do not override other information provided)

NOTES

1. GRADIENTS SHOULD PREFERABLY BE 1:20, 1:14 COULD BE ACCEPTED IN SOME CASES. 1:10 GRADIENT WOULD REQUIRE COUNCIL APPROVAL.
2. PATHS WITHIN PARKS & RESERVES WHERE REQUIRED SHOULD BE OF CONCRETE OR ASPHALT CONSTRUCTION & COMPLY WITH REQUIREMENTS FOR ACCESSIBILITY OF VEHICLES & EQUIPMENT THAT MAY TRAVERSE THE SURFACES FOR AREAS WHERE VEHICLE CROSSING OF PATHS IS REQUIRED, 150MM DEPTH CONCRETE ON 50MM FINE CRUSHED ROCK BASE APPLIES..
3. PATHS WITHIN PLAYGROUNDS SHALL COMPLY WITH PLAYGROUND & DDA DESIGN STANDARDS.
4. PATHS SHALL HAVE A BROOM BRUSHED FINISH WITH HIGHLIGHTED EDGES AND JOINTS.
5. EXPANSION JOINTS TO BE COMPLETED EVERY 9.0 - 10.0 METRES